






POP® Brand

Micro Rivets

- Very low secondary side clearance.
- Suitable for tight spaces.
- Smallest blind breakstem rivet available.
- Low head height.



Nominal Rivet Diameter	(L) Nominal Rivet Body Length	(F) Nominal Blind Side Protrusion	 Grip Range	Rivet Part Number	 Hole Size		 Shear Strength	 Tensile Strength
	In. (mm)	In. (mm)	In. (mm)		In. (mm)		In. (mm)	Lbs. (n)
5154 Aluminum Body/Steel Mandrel – Domed Head – Finish: Plain/Zinc								
.078 (2.0)	.161 (4.1)	.295 (7.5)	0-.063 (0-1.6)	TAPD 20M1 BS	.080-.084 (2.03-2.13)		66 (295)	87 (390)
	.224 (5.7)	.358 (9.1)	.039-.126 (1.0-3.2)	TAPD 20M2 BS				
	.291 (7.4)	.425 (10.8)	.126-.189 (3.2-4.8)	TAPD 20M3 BS				
	.354 (9.0)	.488 (12.4)	.189-.252 (4.8-6.4)	TAPD 20M4 BS				
	.421 (10.7)	.555 (14.1)	.252-.315 (6.4-8.0)	TAPD 20M5 BS				



POP® Brand Rivets In Micro-Electronics Applications

