



Klik-Lok Plastic Rivets

Marson brand Klik-Lok Plastic Rivets are the same precision-molded all-nylon rivets used by domestic auto manufacturers, both for original equipment and replacement parts. In addition, Klik-Lok Plastic Rivets are ideal for non-conductive and non-corrosive environments. Klik-Lok Plastic Rivets fasten plastic to plastic, plastic to metal and plastic to fiberglass. As they set, three “legs” form to securely lock the components in place and prevent pullout.



Plastic rivet before and after

Diagram Reference	100-Pack Part No.*	D Rivet Dia. Nom. Inch	Hole Size Inch	Hole Size (mm)	H Head Dia. Nom. Inch	E Head Height Max. Inch	L Rivet Length Max. Inch	Grip Range Inch	Typical Shear	Ultimate Tensile Strength (Lbs.)
A	48286	.154	.156	(4)	.315	.098	1.024	.236 - .413	40	82
B	48305	.195	.197	(5)	.472	.130	.728	.059 - .177	68	120
C	48306	.195	.197	(5)	.472	.071	.787	.118 - .236	68	120
D	48307	.195	.197	(5)	.472	.071	.787	.118 - .177	68	120
E	48308	.195	.197	(5)	.472	.071	.984	.236 - .394	68	120
F	48309	.195	.197	(5)	.354	.071	.650	.118 - .157	68	120
G	48330	.234	.236	(6.0)	.512	.098	1.102	.157 - .335	110	181
H	48349	.246	.250	(6.3)	.669	.098	.709	.157 - .236	121	194
I	48350	.246	.250	(6.3)	.669	.098	1.102	.157 - .394	121	194
J	48351	.246	.250	(6.3)	.512	.098	1.102	.157 - .394	121	194
K	48353	.246	.250	(6.3)	.670	.098	.682	.028 - .193	121	194
L	48354	.246	.250	(6.3)	.670	.098	.682	.028 - .178	121	194
M	48385	.258	.260	(6.6)	.512	.098	.787	.098 - .197	137	219
N	48386	.258	.260	(6.6)	.709	.098	.787	.098 - .197	137	219

* Also available in bulk 2,000/ctn and visual boxes, 20/pkg.

Actual Size Rivets/Flanges When ordering, match diagram reference letter with those in above chart.

